20

107	- Variation	
1/	ar	9

Course.	Point of Beginning.	Chains Distance.		Corrected Bearings,
East	6/4-31-6	7 41.26	Center Cane march Ditch-This live along a road	
A STATE OF THE STA		41,56	<i>6€ 31</i>	
		83.12	\$1432	2° 35
South	nH-32	22,40	Road crossing	1
		83.53	5%	2 50
East	91/4nnh-32	41.56	8149nh	2°
north	E'4 not	20,88	91432	2° 46
Hest ,	214	H1,59	NN 32	2° 15
South	Cen n of	20.84	6 n n 1 32	24 46
West.	Center	20.83	5/4 NC N 32.	M To
			Jan 17 1898 Surveyed in section 30 I 6 PC 5.	

CORNER ESTABLISHED. Monument. Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. COURSE. in Inches.	Links Distant,	REMARKS.
54 NN-32-6-7 Stone	Gum	24 \$645 €	411/2	
8.25 W. of E4n of blow Goal under				
4,75 n of 814 n of Stone good under				
8.25 9 4.75 nof Eight Stow good under				
of 1/4 Come on a bridge	plone	coalunder pouth	25	
W/4 n M n M limestone coal under	Locust	15 \$149t	106	
It's not limestone coal under	Elm	4 \$198	62%	
Center not limestono goal under		cinder mde bouth	30	
E'4 n A n A Stone good under				
n'4 nh limistore coal unde	The second secon	10 Douth 59 Hest	168	
12,54 9h of 61/4 ngh limestone coalune	ler shoak	8 poutto	62	
	Witness bearing	2 2 /2 var,		

		17.		
64	Ash	12	A 28 %.	884
	Ingar	20	A 444 W	942
ShAEn	Jack Oak	28	87/2 M	71
	Hickory	12	8134,06	592
Center 4 Stone	It Oak	20	Aorth 323 E	384
250ch & of cents "12 ch Ar of above "	go frem	20	0 20 6	14'
2 Ch A of above "				
27.33 A of cents	Houlberry	15-	372 21	912
	B Oak	18	883 €	53-